

PA-4E1G/120 - Cisco 7200 Series Port Adapter

Model: PA-4E1G/120 | Brand: CISCO

Product Overview

Cisco 7200 Series 4-Port E1 G.703 Serial Port Adapter (120ohm/Balanced)

Product page: <https://www.linknewnet.com/products/cisco-pa-4e1g-120-cisco>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	PA-4E1G/120
Series	7200
Ports	4
Port Type	E1 G.703
Impedance	120 ohm
Port Configuration	Balanced
Compatibility	Cisco 7200 Series Routers
Data Rate	2.048 Mbps per port
Connector Type	RJ-48C
Framing	Unframed G.703
Cable Type	Twisted Pair
Supported E1 Lines	CRC4 and non-CRC4
Interface Type	Serial
Form Factor	Plug-in Module
Operating Temperature Range	0 to 40 degrees Celsius
Storage Temperature Range	-40 to 70 degrees Celsius
Humidity Range	10 to 90% non-condensing
Compliance	EN 55022, EN 55024
MTBF	300,000 hours
Product Code	PA-4E1G/120
Brand	CISCO

Replacement / Alternative Options

If the PA-4E1G/120 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
PA-4E1G/75	Cisco 7200 Series 4-Port E1 G.703 Serial Port Adapter (75ohm/Unbalanced)
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of PA-4E1G/120 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).