

Cisco TelePresence MX Series CTS-MX300-K9

Model: CTS-MX300-K9 | Brand: CISCO

Product Overview

Cisco TelePresence MX Series CTS-MX300-K9■MX300 55 Gen 2. PHD 1080p 8x.Touch.Mic

Product page: <https://www.linknewnet.com/products/cisco-telepresence-mx-series-cts-mx300-k9>

Quick Specifications

Attribute	Value
Product Description	Cisco TelePresence MX300 55 Gen 2. PHD 1080p 8x . Touch. Mic
Audio Input Type	Microphone
Audio Output Type	Speaker(s)
Cabinet	Camera, Display, Microphone, Stereo speakers
Image Brightness	450 cd/m²
Image Aspect Ratio	16:9
Response Time	8 ms
Diagonal Size (metric)	139.7 cm
Diagonal Size	55 in
Max Resolution	1920 x 1080
Image Contrast Ratio	4000:1
Type	Network adapter
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Compliant Standards	IEEE 802.1Q, IEEE 802.1x
Features	Flow control, Quality of Service (QoS), SSH support, VLAN support
Transport Protocol	DHCP, DNS, NTP, TCP/IP
Form Factor	External
Capture Resolution	1920 x 1080
Color Support	Color
Product Code	CTS-MX300-K9
Brand	CISCO

Replacement / Alternative Options

If the CTS-MX300-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
CTS-MX700D-2CAM-K9	Cisco TelePresence MX SeriesCTS-MX700D-2CAM-K9 Cisco MX700 Dual 55 Dual Cam.
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of CTS-MX300-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).