

# Cisco TelePresence SX Series Video Conference System CTS-C40CODEC-K9

Model: CTS-C40CODEC-K9 | Brand: CISCO

## Product Overview

CiscoTelePresence Video Conference System ,Video conferencing device

Product page: <https://www.linknewnet.com/products/cisco-telepresence-sx-series-video-conference-system-cts-c40codec-k9>

## Quick Specifications

| Attribute                   | Value                                                                      |
|-----------------------------|----------------------------------------------------------------------------|
| Power cable                 | No                                                                         |
| Button                      | No                                                                         |
| Type                        | Video conferencing device                                                  |
| Digital Signaling Protocol  | H.323, SIP                                                                 |
| Data Compression Protocol   | H.264                                                                      |
| Analog Video Signal         | Composite video (NTSC, PAL)                                                |
| Digital Video Standard      | Digital Visual Interface (DVI), High-Definition Multimedia Interface (HDM) |
| Connectivity Technology     | Ethernet, Fast Ethernet, Gigabit Ethernet                                  |
| Network/Transport Protocol  | TCP/IP                                                                     |
| Features                    | Flow control, firewall protection, DHCP support, Quality of Service (QoS)  |
| Width                       | 17.4 in                                                                    |
| Height                      | 1.7 in                                                                     |
| Depth                       | 10.9 in                                                                    |
| Weight                      | 8.82 lbs                                                                   |
| Power Device                | Power supply - internal                                                    |
| Voltage Required            | AC 120/230 V (50/60 Hz)                                                    |
| Power Consumption Operating | 175 Watt                                                                   |
| Min Operating Temperature   | 32 °F                                                                      |
| Max Operating Temperature   | 95 °F                                                                      |
| Humidity Range Operating    | 10 - 90% (non-condensing)                                                  |
| Product Code                | CTS-C40CODEC-K9                                                            |
| Brand                       | CISCO                                                                      |

## Replacement / Alternative Options

If the CTS-C40CODEC-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

| Model                           | Specification                                                                       |
|---------------------------------|-------------------------------------------------------------------------------------|
| <a href="#">WS-X6816-10G-2T</a> | Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module |

|           |                                                                             |
|-----------|-----------------------------------------------------------------------------|
| WS-C4948E | Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC |
|-----------|-----------------------------------------------------------------------------|

Request availability: [Ask for current stock](#) of CTS-C40CODEC-K9 or its alternatives.

## Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).