

Cisco TelePresence System Codec C60

CTS-C60CODEC-K9

Model: CTS-C60CODEC-K9 | Brand: CISCO

Product Overview

Cisco TelePresence System Codec C60 CTS-C60CODEC-K9

Product page: <https://www.linknewnet.com/products/cisco-telepresence-system-codec-c60-cts-c60codec-k9>

Quick Specifications

Attribute	Value
Product Type	Video conferencing device
Digital Signaling Protocol	H.323, SIP
Data Compression Protocol	H.264
Digital Video Standard	Digital Visual Interface (DVI), High-Definition Multimedia Interface (HDMI)
Network/Transport Protocol	TCP/IP
Voice output	Codec board
Network Protocols	Network Protocols
Compliant Standards	EN 61000-3-2, EN 61000-3-3, EN55024, EN55022 Class B, FCC Part 15 B, UL 60950-1, EN 60950-1, CSA C22.2 No. 60950-1-07
Power Device	Power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Width	17.4 in
Depth	10.9 in
Height	1.7 in
Weight	8.82 lbs
Min Operating Temperature	32 °F
Max Operating Temperature	95 °F
Humidity Range Operating	10 - 90%
Product Code	CTS-C60CODEC-K9
Brand	CISCO

Replacement / Alternative Options

If the CTS-C60CODEC-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module
WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC

Request availability: [Ask for current stock](#) of CTS-C60CODEC-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).