

CISCO1921/K9 - Cisco 1921 Series Integrated Services Routers

Model: CISCO1921/K9 | Brand: CISCO

Product Overview

Cisco ISR 1900 Series, 1921 Modular Router, 2 GE ports, 2 EHWIC slots, 512MB DRAM, IP Base license included.

Product page: <https://www.linknewnet.com/products/cisco1921-k9>

Quick Specifications

Attribute	Value
RJ-45 onboard LAN/WAN 10/100/1000 ports	2
EHWIC slots	2
Memory (DDR2 DRAM): Default/maximum	512 MB/512 MB
Serial console port (up to 115.2 kbps)	1
Serial auxiliary port (up to 115.2 kbps)	1
Integrated power supply	AC and DC power-supply models
Power-supply options	POE (external) - on AC models only
Redundant-power-supply support	No
AC input voltage	100-240V ~
AC input frequency	47-63 Hz
AC input surge current	<50A
Typical power (no modules)	25W
DC power input	32-60 VDC, 4A, positive or negative, single source
DC input wire size	AWG 14 (2.0 mm ²)
Safety ground-wire size	AWG 14 (2.0 mm ²), minimum
Wire terminal (lug)	Amp/Tyco No.32957
Overcurrent protection	20A maximum
Dimensions (H x W x D)	1.75 x 13.5 x 11.5 in. (4.45 x 34.29 x 29.21 cm)
Rack height	1 rack unit (1RU)
Rack-mount 19 in. (48.3 cm) EIA	Optional
Product Code	CISCO1921/K9
Brand	CISCO

Replacement / Alternative Options

If the CISCO1921/K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
CISCO1801	ADSL/POTS router w/IOS IP Broadband
CISCO1801-M/K9	CISCO1801 Security Router with Annex M

Request availability: [Ask for current stock](#) of CISCO1921/K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).