

CISCO2921/K9 - Cisco 2900 Series Integrated Service Router

Model: CISCO2921/K9 | Brand: CISCO

Product Overview

Cisco 2921 Router w/3 GE,4 EHWIC,3 DSP,1 SM,256MB CF,512MB DRAM,IPB

Product page: <https://www.linknewnet.com/products/cisco2921-k9>

Quick Specifications

Attribute	Value
Device Type	Router
Enclosure Type	Rack-mountable - modular - 2U
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Network / Transport Protocol	IPSec, L2TPv3
Remote Management Protocol	SNMP, RMON, TR-069
Compliant Standards	IEEE 802.3, IEEE 802.1Q, IEEE 802.3af, IEEE 802.3ah, IEEE 802.1ah, IEEE 802.1ag, ANSI T1.101, ITU-T G.823, ITU-T G.824
RAM	512 MB (installed) / 2 GB (max)
Flash Memory	256 MB (installed) / 8 GB (max)
Status Indicators	Link activity, power
Expansion Slot(s)	4 (total) / 4 (free) x HWIC 3 (total) / 3 (free) x PVDM 2 (total) / 1 (free) x CompactFlash Card 1 (total) / 1 (free) x expansion slot
Power Device	Power supply - internal
Voltage Required	AC 120/230 V (50/60 Hz)
Dimensions (W x D x H)	17.2 x 18.5 x 3.5 in (47 x 43.8 x 8.9 cm)
Package Weight	41.7 lbs (18.93 Kg)
Weight	29.1 lbs (13.2 Kg)
Rack Mounting Kit	N/A
Service & Support	90 days warranty
Product Code	CISCO2921/K9
Brand	CISCO

Replacement / Alternative Options

If the CISCO2921/K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
CISCO2811	CISCO 2800 Series Router CISCO2811 w/AC PWR, 2FE, 4HWICs, 2PVDMs, 1NME, 2AIMS, IP BASE, 64F/256D
CISCO2901/K9	CISCO 2900 Series Integrated Services RouterCISCO2901/K94 EHWIC slots, 2 DSP slots, 1 ISM slot, 256MB CF default ,512MB DRAM default, IP Base

Request availability: [Ask for current stock](#) of CISCO2921/K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).