

CISCO3925E-V/K9 - Cisco 3900 Series Integrated Service Router

Model: CISCO3925E-V/K9 | Brand: CISCO

Product Overview

Cisco 3925E Voice Bundle, PVDM3-64, UC License PAK

Product page: <https://www.linknewnet.com/products/cisco3925e-v-k9>

Quick Specifications

Attribute	Value
Bundle	Cisco 3925E Voice Bundle, PVDM3-64, UC License PAK
Cisco Unified SRST sessions	1350
RJ-45-based ports	4
SFP-based ports	2
Service-module slots	2
Doublewide service-module slots	1
EHWIC slots	3
Doublewide EHWIC slots	1
ISM slots	0
Online insertion and removal (OIR)	Services modules
Onboard DSP (PVDM) slots	3
Memory DDR2 ECC DRAM: Default	1 GB
Memory DDR2 ECC DRAM: Maximum	2 GB
Compact Flash (external): Default	Slot 0: 256 MB
Compact Flash (external): Maximum	Slot 0: 4 GB
External USB 2.0 slots (Type A)	2
Serial console port (up to 115.2 kbps)	1
Power-supply options	Internal : AC, PoE, and DC*
Redundant power supply	Internal: AC, PoE, and DC*
AC input voltage	100 to 240 VAC autoranging
Product Code	CISCO3925E-V/K9
Brand	CISCO

Replacement / Alternative Options

If the CISCO3925E-V/K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
CISCO3825	3825 w/AC PWR, 2GE,1SFP, 2NME, 4HWIC, IP Base, 128F/512D
CISCO3825-AC-IP	3825 w/AC+POE,2GE,1SFP, 2NME, 4HWIC, IP Base, 128F/512D

Request availability: [Ask for current stock](#) of CISCO3925E-V/K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).