

CPAK-100G-PSM4= - Cisco QSFP28 Module

Model: CPAK-100G-PSM4= | Brand: CISCO

Product Overview

CPAK optical transceiver module, PSM4 500m SMF, parallel

Product page: <https://www.linknewnet.com/products/cpak-100g-psm4>

Quick Specifications

Attribute	Value
Description	100GBASE PSM4 Cisco CPAK Module for SMF
Dimensions	11.6 x 34.8 x 101.2 mm (0.46 x 1.37 x 3.98 in)
Wavelength (nm)	1295 to 1325
Cable Type	SMF (12 fibers)
Core Size (Microns)	9-micron core SMF per G.652
Modal Bandwidth (MHz*km)	\
Cable Distance	500 m
Type	100GBASE PSM4 SMF
Transmit Power	Max:+2.0 per lane Min:-9.4 per lane
Receive Power (dBm)	Max:+9.4 per lane Min:-2.0 per lane
Supported Mode	1x100G
Supported Protocol	IEEE 802.3ba
Storage temperature	-40 to 85° C (-40 to 185° F)
Operating temperature	0 to 70 ° C (32 to 158 ° F)
P ower consumption	At 70 ° C: < 9.0W maximum
Product Code	CPAK-100G-PSM4=
Brand	CISCO

Replacement / Alternative Options

If the CPAK-100G-PSM4= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
CPAK-100G-CWDM4=	CPAK optical transceiver module,100G, CWDM4, 2km SMF
CPAK-100G-ER4L=	CPAK module, 100G for applications <25km

Request availability: [Ask for current stock](#) of CPAK-100G-PSM4= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).