

CPAK-100G-SR10= - Cisco QSFP28 Module

Model: CPAK-100G-SR10= | Brand: CISCO

Product Overview

CPAK-100G-SR10 Transceiver module, 100m OM3 MMF

Product page: <https://www.linknewnet.com/products/cpak-100g-sr10>

Quick Specifications

Attribute	Value
Description	100GBASE-SR10 Cisco CPAK Module for MMF
Dimensions	11.6 x 34.8 x 101.2 mm (0.46 x 1.37 x 3.98 in)
Wavelength (nm)	850
Cable Type	MMF (12 fibers)
Core Size (Microns)	50.0 50.0
Cable Distance	100 m 150 m
Modal Bandwidth (MHz*km)	2000 (OM3) 4700 (OM4)
Type	100GBASE-SR10 850 nm MMF
Transmit Power	Max:+1.0 per lane Min:-7.6 per lane
Receive Power (dBm)	Max:+2.4 per lane Min:-9.5 per lane
Supported Mode	Supported Protocol
1x100G	IEEE 802.3ba ITU OTU4
2x40G	IEEE 802.3ba ITU OTU3
10x10G	IEEE 802.3ae FC ITU OTU2 ITU OTU1e ITU OTU2e
Storage temperature	-40 to 85° C (-40 to 185° F)
Operating temperature	0 to 70 ° C (32 to 158 ° F)
P ower consumption	At 70 ° C: < 4.5 W maximum
Product Code	CPAK-100G-SR10=
Brand	CISCO

Replacement / Alternative Options

If the CPAK-100G-SR10= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
CPAK-100G-CWDM4=	CPAK optical transceiver module,100G, CWDM4, 2km SMF
CPAK-100G-ER4L=	CPAK module, 100G for applications <25km

Request availability: [Ask for current stock](#) of CPAK-100G-SR10= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).