Mikrotik CSS326-24G-2S+RM

Model: CSS326-24G-2S+RM | Brand: MikroTik

Product Overview

CSS326-24G-2S+RM SwOS powered 24 port Gigabit Ethernet switch with two SFP+

Product page: https://www.linknewnet.com/products/css326-24g-2s+rm

Quick Specifications

Attribute	Value
Switch chip model	98DX3216
Dimensions	443 x 144 x 44 mm
Operating System	SwOS
Storage size	2 MB
Storage type	FLASH
MTBF	Approximately 200'000 hours at 25C
Tested ambient temperature	-20°C to 70°C
Number of DC inputs	2 (DC jack, PoE-IN)
DC jack input Voltage	10-30 V
Max power consumption	19 W
PoE in	Passive PoE
Cooling type	Passive
PoE in input Voltage	10-30 V
10/100/1000 Ethernet ports	24
SFP+ ports	2
Product Code	CSS326-24G-2S+RM
Brand	MikroTik

Replacement / Alternative Options

If the CSS326-24G-2S+RM is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
CRS305-1G-4S+IN	MikroTik CRS305-1G-4S+IN Network switch manages Gigabit Ethernet (10/100/1000) and Power over Ethernet (PoE)
CRS310-1G-5S-4S+IN	Mikrotik CRS310-1G-5S-4S+IN 5 SFP ports 4 SFP+ ports and 1 Gigabit Ethernet port

Request availability: Ask for current stock of CSS326-24G-2S+RM or its alternatives.

Buying from LinkNewNet

Every unit is fully tested (ports verified, firmware validated) and covered by warranty.