MikroTik CSS610-8G-2S+IN

Model: CSS610-8G-2S+IN | Brand: MikroTik

Product Overview

MikroTik CSS610-8G-2S+IN 8-Port Gigabit Switch + 2x 10G SFP+ Fibre Uplink

Product page: https://www.linknewnet.com/products/css610-8g-2s+in

Quick Specifications

Attribute	Value
Switch chip model	88E6193X
Dimensions	200 x 164 x 44 mm
Operating System	SwitchOS Lite
Storage size	64 KB
Storage type	FLASH
MTBF	Approximately 200'000 hours at 25C
Tested ambient temperature	-20°C to 60°C
Number of DC inputs	2 (DC jack, PoE-IN)
DC jack input Voltage	12-57 V
Max power consumption	11 W
PoE in	Passive PoE
Cooling type	Passive
PoE in input Voltage	12-57 V
10/100/1000 Ethernet ports	8
SFP+ ports	2
Product Code	CSS610-8G-2S+IN
Brand	MikroTik

Replacement / Alternative Options

If the CSS610-8G-2S+IN is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
CSS610-8P-2S+IN	Mikrotik CSS610-8P-2S+IN PoE Powerhouse with 8x Gigabit PoE SFP+
CRS305-1G-4S+IN	MikroTik CRS305-1G-4S+IN Network switch manages Gigabit Ethernet (10/100/1000) and Power over Ethernet (PoE)

Request availability: Ask for current stock of CSS610-8G-2S+IN or its alternatives.

Buying from LinkNewNet

Every unit is fully tested (ports verified, firmware validated) and covered by warranty.