

Cisco CW9162I-x

Model: CW9162I-x | Brand: CISCO

Product Overview

Catalyst 9100

Product page: <https://www.linknewnet.com/products/cw9162i-x>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	CW9162I-x
Series	Catalyst 9100
Wi-Fi Standard	Wi-Fi 6 (802.11ax)
Frequency Bands	Dual-band 2.4 GHz and 5 GHz
Antenna Type	Internal Antennas
Maximum Data Rate	5.2 Gbps
Ports	1x 2.5GBASE-T, 1x USB
Ethernet	10/100/1000/2500 Mbps
Dimensions	8.3 x 8.3 x 1.5 in.
Enclosure Type	Plenum-rated, 0-U mRail
Operating Temperature Range	-4??F to 131??F (-20??C to 55??C)
Compliance	FCC, IC, CE
MIMO	4x4:4
Power Supply Options	802.3at PoE, local power supply
Security Standards	WPA3
Management	Cisco DNA Center, Embedded Wireless Controller
Encryption	AES
Maximum Clients	1000
LED Indicators	Multi-color
Product Code	CW9162I-x
Brand	CISCO

Replacement / Alternative Options

If the CW9162I-x is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module
WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC

Request availability: [Ask for current stock](#) of CW9162I-x or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).