

Cisco DS-C9706

Model: DS-C9706 | Brand: CISCO

Product Overview

Cisco MDS 9706 Multilayer Director

Product page: <https://www.linknewnet.com/products/ds-c9706>

Quick Specifications

Attribute	Value
Brand	Cisco
Model Number	DS-C9706
Chassis Height	9 Rack Units
Switch Fabric Capacity	Up to 6.1 Tbps
Ports per Module	Up to 48
Total Ports	Up to 192
Supervisor Engines	Dual
Protocol Support	FCoE, FCIP, iSCSI
Operating Temperature	32??F to 104??F (0??C to 40??C)
Storage Temperature	-40??F to 158??F (-40??C to 70??C)
Humidity	10% to 90% (non-condensing)
Power Supply	100-240 VAC, 50-60 Hz
Maximum Power Consumption	4000W
Cooling	Front-to-back airflow
Dimensions (H x W x D)	15.75 x 17.98 x 24.6 inches (40 x 45.7 x 62.5 cm)
Weight	Not Specified
Management	CLI, SNMP, RMON, HTTP
Software Compatibility	Cisco NX-OS
Redundancy	Yes
Compliance	RoHS, CE, FCC
Product Code	DS-C9706
Brand	CISCO

Replacement / Alternative Options

If the DS-C9706 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
DS-C9710-1K9	MDS 9710 Base Config Chassis FANs 2 Sup-1 3 Fab-1 6 PS AC 3K
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of DS-C9706 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).