

EX2300-24P-VC - Juniper EX2300 Series Ethernet Switches

Model: EX2300-24P-VC | Brand: Juniper

Product Overview

EX2300 24-PORT POE+ W/ VC LICENSE

Product page: <https://www.linknewnet.com/products/ex2300-24p-vc>

Quick Specifications

Attribute	Value
Brand	Juniper
Model	EX2300-24P-VC
Ports	24 x 10/100/1000Base-T PoE+ ports
PoE Power Budget	370W
Virtual Chassis	Supports up to 4-member Virtual Chassis
Layer	Layer 2 and Layer 3
Switching Capacity	56 Gbps
Forwarding Rate	41.67 Mpps
Jumbo Frames	Up to 9216 Bytes
Management	CLI, Web GUI, SNMP
Redundancy	Hot-swappable power supplies and fans
QoS	8 QoS queues
Security	802.1X, DHCP snooping, Dynamic ARP inspection
Dimensions (WxDxH)	17.4 x 10.0 x 1.7 inches
Max Power Consumption	431W
Operating Temperature	32°F to 104°F (0°C to 40°C)
Operating Humidity	10% to 85% (non-condensing)
Storage Temperature	-40°F to 158°F (-40°C to 70°C)
Storage Humidity	5% to 95% (non-condensing)
Acoustic Noise	Less than 43 dB
Product Code	EX2300-24P-VC
Brand	Juniper

Replacement / Alternative Options

If the EX2300-24P-VC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
EX2300-24MP	Juniper EX2300 8x1GbE/2.5GbE + 16x1GbE Ethernet Switch
EX2300-24P	EX2300 24-port 10/100/1000BaseT PoE+, 4 x 1/10G SFP/SFP+ (optics sold separately)

Request availability: [Ask for current stock](#) of EX2300-24P-VC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).