

FPR2120-K9= - Cisco Used Firepower 2100 Series

Model: FPR2120-K9= | Brand: CISCO

Product Overview

Firepower 2120 appliance 1 RU with no power supply or fan (spare)

Product page: <https://www.linknewnet.com/products/fpr2120-k9>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	FPR2120-K9=
Type	Firewall Appliance
Form Factor	1 RU
Ethernet Ports	8 x 1 GE RJ45, 8 x 1 GE SFP
Management Ports	2 x 1 GE RJ45, 1 x 1 GE SFP
Maximum Throughput	8 Gbps
Maximum Concurrent Sessions	4 million
Maximum VPN Peers	10,000
Network Management	Centralized Management through Cisco Firepower Management Center
Power Supply	Not included
Fan	Not included
Hardware Bypass	Yes
Security Features	Threat Protection, URL Filtering, Application Control, Malware Defense
Physical Dimensions	1.72" x 16.89" x 18.13";
Rack Mounting Kit	Included
Operating Temperature Range	32°F to 104°F (0°C to 40°C)
Storage Temperature Range	-13°F to 158°F (-25°C to 70°C)
Humidity (Operating)	10% to 90% non-condensing
Humidity (Storage)	5% to 95% non-condensing
Product Code	FPR2120-K9=
Brand	CISCO

Replacement / Alternative Options

If the FPR2120-K9= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
FPR2120-ASA-K9	Cisco Firepower 2120 ASA Appliance. 1U
FPR2120-FTD-HA-BUN	Cissco Firepower 2120 Threat Defense Chss,Subs HA Bundle

Request availability: [Ask for current stock](#) of FPR2120-K9= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).