

FPR2130-ASA-K9 - Cisco Used Firepower 2100 Series

Model: FPR2130-ASA-K9 | Brand: CISCO

Product Overview

Cisco Firepower 2130 ASA Appliance. 1U. 1 x NetMod Bay

Product page: <https://www.linknewnet.com/products/fpr2130-asa-k9>

Quick Specifications

Attribute	Value
Stateful inspection firewall throughput	10 Gbps
Concurrent firewall connections	2 million
New connections per second	40000
Maximum number of VLANs	750
Security contexts (included; maximum)	2; 30
High availability	Active/active and active/standby
Scalability	VPN Load Balancing
Adaptive Security Device Manager	Web-based, local management for small-scale deployments
Dimensions (H x W x D)	1.73 x 16.90 x 19.76 in. (4.4 x 42.9 x 50.2 cm)
Form factor (rack units)	1RU
I/O module slots	1 NM slot
Integrated I/O	12 x 10M/100M/1GBASE-T Ethernet interfaces (RJ-45), 4 x 10 Gigabit (SFP+) Ethernet interfaces
Network modules	(FPR-NM-8X10G) 8 x 10 Gigabit Ethernet Enhanced Small Form-Factor Pluggable (SFP+) network module
Maximum number of interfaces	Up to 24 total Ethernet ports (12x1G RJ-45, 4x10G SFP+, and network module with 8x10G SFP+)
Integrated network management ports	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)
Serial port	1 x RJ-45 console
USB	1 x USB 2.0 Type-A (500mA)
Storage	1x 200 GB, 1x spare slot (for MSP)
Power supplies	Configuration Single integrated 250W AC power supply.
AC input voltage	100 to 240V AC
Product Code	FPR2130-ASA-K9
Brand	CISCO

Replacement / Alternative Options

If the FPR2130-ASA-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
FPR2130-NGFW-K9	Cisco Firepower 2130 NGFW Appliance. 1U. 1 x NetMod Bay, Firepower 2100 series
FPR2130-ASA-K9-CAP	Cisco Firepower 2130 ASA Appl, 1U, 1 NetMod, 5Y SNT Support

Request availability: [Ask for current stock](#) of FPR2130-ASA-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).