

FPR2130-K9= - Cisco Used Firepower 2100 Series

Model: FPR2130-K9= | Brand: CISCO

Product Overview

Firepower 2130 appliance with 1 network module bay and no power supply or fan (spare)

Product page: <https://www.linknewnet.com/products/fpr2130-k9>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	FPR2130-K9=
Product Type	Security Appliance
Series	Firepower 2100 Series
Network Module Bay	1
Power Supply	None (spare)
Fan	None (spare)
Firewall Throughput	5 Gbps (4500/2200 SSL VPN)
Maximum Concurrent Connections	2 million
New Connections per Second	170,000
Threat Protection Throughput	3 Gbps
Maximum VPN Peers	5,000
Form Factor	1U Rack-Mountable
Dimensions (H x W x D)	1.72 x 17.3 x 21.75 inches
Operating Temperature	32 to 104°F (0 to 40°C)
Storage Temperature	-4 to 158°F (-20 to 70°C)
Humidity (operating)	10% to 85% RH
Humidity (non-operating)	5% to 95% RH
Certifications	FIPS 140-2, Common Criteria, ICSA Firewall, ICSA IPsec
Redundant Power Supply	Optional
Product Code	FPR2130-K9=
Brand	CISCO

Replacement / Alternative Options

If the FPR2130-K9= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
FPR2130-NGFW-K9	Cisco Firepower 2130 NGFW Appliance. 1U. 1 x NetMod Bay, Firepower 2100 series
FPR2130-ASA-K9	Cisco Firepower 2130 ASA Appliance. 1U. 1 x NetMod Bay

Request availability: [Ask for current stock](#) of FPR2130-K9= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).