

FPR2K-PWR-AC-400 - Cisco Used Firepower 2100 Series

Model: FPR2K-PWR-AC-400 | Brand: CISCO

Product Overview

400W AC power supply

Product page: <https://www.linknewnet.com/products/fpr2k-pwr-ac-400>

Quick Specifications

Attribute	Value
Power Output	400W
Input Voltage Range	100-240V AC
Frequency Range	50-60 Hz
Efficiency	88% typical
Form Factor	Plug-in module
Compatible Products	Cisco Firepower 2100 Series
Heat Dissipation	1365 BTU/hr
Operating Temperature	0°C to 40°C
Storage Temperature	-20°C to 70°C
Relative Humidity	10% to 90% non-condensing
Altitude	0 to 3000 meters
Cooling	Integrated fan
Dimensions (HxWxD)	40 x 101 x 360 mm
Power Cord Type	IEC 60320 C13
Compliance	RoHS, WEEE
LED Indicators	Power, Status
Noise Level	46 dB(A) max
MTBF	200,000 hours
Redundancy Support	Hot-swappable
Warranty	1 year limited
Product Code	FPR2K-PWR-AC-400
Brand	CISCO

Replacement / Alternative Options

If the FPR2K-PWR-AC-400 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
FPR2K-CBL-MGMT	Cable management brackets
FPR2K-CBL-MGMT=	Cable management brackets (spare)

Request availability: [Ask for current stock](#) of FPR2K-PWR-AC-400 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).