

FPR2K-PWR-DC-350 - Cisco Used Firepower 2100 Series

Model: FPR2K-PWR-DC-350 | Brand: CISCO

Product Overview

350W DC power supply

Product page: <https://www.linknewnet.com/products/fpr2k-pwr-dc-350>

Quick Specifications

Attribute	Value
Power Capacity	350W
Input Voltage Range	-48V DC to -60V DC
Output Voltage	12V DC
Efficiency	90%
Cooling Type	Internal Fan
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Humidity Range	10% to 90% (non-condensing)
Dimensions (W x D x H)	8.5 in x 11 in x 1.5 in
MTBF	500,000 hours
Connector Type	Terminal Block
Certification	CE, UL, CSA, FCC
Protection Features	Overload, Short Circuit, Over Voltage
Compatibility	Cisco Firepower 2100 Series
Color	Silver
LED Indicators	Power Status
Hot Swappable	Yes
Altitude	Up to 10,000 feet
RoHS Compliance	Yes
Warranty	1 Year
Product Code	FPR2K-PWR-DC-350
Brand	CISCO

Replacement / Alternative Options

If the FPR2K-PWR-DC-350 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
FPR2K-CBL-MGMT	Cable management brackets
FPR2K-CBL-MGMT=	Cable management brackets (spare)

Request availability: [Ask for current stock](#) of FPR2K-PWR-DC-350 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).