

IR1101-K9 - Cisco IR1101 Integrated Services Router Rugged

Model: IR1101-K9 | Brand: CISCO

Product Overview

Cisco Catalyst IR1101 Rugged Series Router with SL-IR1101-NE software license

Product page: <https://www.linknewnet.com/products/ir1101-k9>

Quick Specifications

Attribute	Value
Cisco IOS Software requirements	● Cisco IOS XE Software: Universal Cisco IOS Software image ● Cisco IOS XE Software Release 16.10.1 or later
Default and maximum DRAM	4 GB
Default and maximum Flash memory	4 GB (usable)
Ingress protection rating	IP30
Physical dimensions (H x W x D) Chassis	2.36 in. x 5.22 in. x 4.92 in. (60 x 132.5 x 124.9 mm)
Weight (Chassis)	2.25 lbs (1.02 kg)
Mounting options	Panel, wall, and din rail (vertical and horizontal) mount
Power consumption	At idle: 6.6W Typical: 9.8W Maximum: 12W Additional 10W (typical) with expansion module and 2nd cellular
Console	Mini type-B USB
LAN interfaces	● Four 10/100BASE-T Fast Ethernet ports
Input and output	● ALARM input port
Operating altitude	40°C up to 13,800 ft (operating) per IEC 68-2-41
Non-operating temperature	-40 to 185°F (-40 to 85°C)
Product Code	IR1101-K9
Brand	CISCO

Replacement / Alternative Options

If the IR1101-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
IR1101-K9-DNA	Cisco IR1101 DNAC Industrial ISR Rugged
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of IR1101-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).