

Cisco Router ISR 4000 Series ISR4351-V/K9

Model: ISR4351-V/K9 | Brand: CISCO

Product Overview

200Mbps-400Mbps system throughput, 3 WAN/LAN ports, 3 SFP ports, multi-Core CPU, 2 service module slots, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC

Product page: <https://www.linknewnet.com/products/isr4351-v-k9>

Quick Specifications

Attribute	Value
Description	Cisco ISR4351-V/K9 (3GE, 3NIM, 2SM, 4G FLASH, 4G DRAM, Voice Bundle)
Aggregate Throughput	200 Mbps to 400 Mbps
RJ-45-based ports	3
SFP-based ports	3
Enhanced service-module slots	2
Doublewide service-module slots	1 (assumes no singlewide SM-X modules installed)
NIM slots	3
OIR (all I/O modules)	Yes
Onboard ISC slot	1
Default flash memory	4 GB
Maximum flash memory	16 GB
External USB 2.0 slots (type A)	2
Power-supply options	Internal: AC, DC, and PoE
Redundant power supply	N/A
AC input voltage	100 to 240 VAC autoranging
AC input frequency	47 to 63 Hz
AC input surge current	60 A peak and less than 12 Arms per half cycle
Typical power (no modules) (watts)	48
Product Code	ISR4351-V/K9
Brand	CISCO

Replacement / Alternative Options

If the ISR4351-V/K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
ISR4351-AX/K9	Cisco ISR 4351 AX Bundle w/ APP.SEC lic
ISR4351-AXV/K9	Cisco ISR 4351 AXV Bundle.PVDM4-64 w/APP.SEC.UC lic.CUBE-25

Request availability: [Ask for current stock](#) of ISR4351-V/K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).