

Cisco Router ISR 4000 Series ISR4431-V/K9

Model: ISR4431-V/K9 | Brand: CISCO

Product Overview

500Mbps-1Gbps system throughput, 4 WAN/LAN ports, 4 SFP ports, multi-Core CPU, Dual-power, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC, separate control data and services CPUs

Product page: <https://www.linknewnet.com/products/isr4431-v-k9>

Quick Specifications

Attribute	Value
Description	Cisco ISR 4431 (4GE, 3NIM, 8G FLASH, 4G DRAM, VOIP)
Aggregate Throughput	500Mbps to 1Gbps
RJ-45-based ports	4
SFP-based ports	4
Enhanced service-module slots	0
Doublewide service-module slots	0
NIM slots	3
OIR (all I/O modules)	Yes
Onboard ISC slot	1
Default flash memory	8 GB
Maximum flash memory	32 GB
External USB 2.0 slots (type A)	2
Power-supply options	Internal: AC, DC, and PoE
Redundant power supply	Internal: AC, DC, and PoE
AC input voltage	100 to 240 VAC autoranging
AC input frequency	47 to 63 Hz
AC input surge current	60 A peak and less than 5 Arms per half cycle
Typical power (no modules) (watts)	65
Product Code	ISR4431-V/K9
Brand	CISCO

Replacement / Alternative Options

If the ISR4431-V/K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
ISR4431-AX/K9	500Mbps-1Gbps system throughput, 4 WAN/LAN ports, 4 SFP ports, multi-Core CPU, Dual-power, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC, separat

ISR4431-AXV/K9	Cisco ISR 4431 AXV Bundle.PVDM4-64 w/APP.SEC.UC lic.CUBE-25
----------------	---

Request availability: [Ask for current stock](#) of ISR4431-V/K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).