

Cisco Router ISR 4000 Series ISR4461-AX/K9

Model: ISR4461-AX/K9 | Brand: CISCO

Product Overview

Cisco ISR 4461 with AppX license

Product page: <https://www.linknewnet.com/products/isr4461-ax-k9>

Quick Specifications

Attribute	Value
Bundle	AppX License
Aggregate Throughput	1.5Gbps
RJ-45-based ports	4
SFP-based ports	4
Enhanced service-module slots	3
Doublewide service-module slots	2
NIM slots	3
OIR (all I/O modules)	Yes
Onboard ISC slot	1
Default flash memory	8 GB
Maximum flash memory	32 GB
External USB 2.0 slots (type A)	2
Power-supply options	Internal: AC, DC and PoE
Redundant power supply	Internal: AC, DC and PoE
AC input voltage	100 to 240 VAC auto ranging
AC input frequency	47 to 63 Hz
AC input surge current	60 A peak and less than 5 Arms per half cycle
Typical power (no modules) (watts)	-
Dimensions (H x W x D)	3.5 x 17.25 x 18.5 in 88.9 x 438.15 x 469.9 mm)
Rack height	2 Rack Units (2RU)
Product Code	ISR4461-AX/K9
Brand	CISCO

Replacement / Alternative Options

If the ISR4461-AX/K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
ISR4461-AXV/K9	Cisco ISR 4461 AXV Bundle

ISR4461-SEC/K9	Cisco ISR 4461 Security Bundle
----------------	--------------------------------

Request availability: [Ask for current stock](#) of ISR4461-AX/K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).