

Juniper EX-SFP-FE20KT15R13 Switches

Model: Juniper EX-SFP-FE20KT15R13 | Brand: Juniper

Product Overview

SFP 100Base-BX Fast Ethernet Optics, Tx 1550nm/Rx 1310nm for 20km transmission

Product page: <https://www.linknewnet.com/products/juniper-ex-sfp-fe20kt15r13>

Quick Specifications

Attribute	Value
Brand	Juniper
Product Name	Juniper EX-SFP-FE20KT15R13
Form Factor	SFP
Type	100Base-BX Fast Ethernet Optics
Transmission Distance	Up to 20 km
Transmitter Wavelength	1550 nm
Receiver Wavelength	1310 nm
Compatible Cable Type	Single-mode Fiber (SMF)
DOM Support	Yes
Connector Type	LC Duplex
Max Data Rate	100 Mbps
Temperature Range	0 to 70°C (32 to 158°F)
Power Consumption	Less than 1W
Compliance	MSA Compliant
TX Output Power	-3 to -9 dBm
RX Sensitivity	< -20 dBm
Saturation Optical Power	> -3 dBm
Extinction Ratio	9 dB
Certification	RoHS Compliant
Application	Fast Ethernet, Metro access rings, Point-to-point networking
Product Code	Juniper EX-SFP-FE20KT15R13
Brand	Juniper

Replacement / Alternative Options

If the Juniper EX-SFP-FE20KT15R13 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.
Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG

Request availability: [Ask for current stock](#) of Juniper EX-SFP-FE20KT15R13 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).