

Juniper EX-UM-2QSFP-MR Switches

Model: Juniper EX-UM-2QSFP-MR | Brand: Juniper

Product Overview

EX4300-48MP, 2-Port 40G QSFP+/2-Port 100G QSFP28 Uplink Module

Product page: <https://www.linknewnet.com/products/juniper-ex-um-2qsfp-mr>

Quick Specifications

Attribute	Value
Brand	Juniper
Model	EX-UM-2QSFP-MR
Compatible Models	EX4300-48MP
Uplink Ports	2 x 40G QSFP+, 2 x 100G QSFP28
Form Factor	Module
Port Speed	40G, 100G
Port Type	QSFP+, QSFP28
Data Transfer Rate	40 Gbps, 100 Gbps
Hot Swap	Yes
Operating Temperature	0°C to 45°C (32°F to 113°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Relative Humidity (Operating)	10% to 85% (non-condensing)
Relative Humidity (Storage)	10% to 90% (non-condensing)
Dimensions (H x W x D)	1.25 x 5.0 x 12.0 inches
Compliance	RoHS-6
Power Consumption	10W (typical)
Cooling	Air-cooled
Warranty	1 Year
MTBF	2,000,000 hours
Regulatory Approvals	FCC, CE, UL
Product Code	Juniper EX-UM-2QSFP-MR
Brand	Juniper

Replacement / Alternative Options

If the Juniper EX-UM-2QSFP-MR is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.
Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG

Request availability: [Ask for current stock](#) of Juniper EX-UM-2QSFP-MR or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).