

Juniper EX2300-C-12P-VC Switches

Model: Juniper EX2300-C-12P-VC | Brand: Juniper

Product Overview

EX2300 Compact Fanless 12-port 10/100/1000BaseT PoE+, 2 x 1/10G SFP/SFP+ with VC License (optics sold separately)

Product page: <https://www.linknewnet.com/products/juniper-ex2300-c-12p-vc>

Quick Specifications

Attribute	Value
Brand	Juniper
Model	EX2300-C-12P-VC
Form Factor	Compact, Fanless
Ports	12 x 10/100/1000BaseT
Power over Ethernet (PoE)	PoE+
Uplink Ports	2 x 1/10G SFP/SFP+
Virtual Chassis	Supported with VC License
Optics	Sold separately
Layer Support	Layer 2 and Layer 3
Switching Capacity	56 Gbps
Forwarding Rate	41.67 Mpps
MAC Address Table Size	16K entries
Flash Memory	2 GB
DRAM	2 GB
Dimension (W x D x H)	10.4 x 9.4 x 1.75 inches
Operating Temperature	0°C to 45°C
Storage Temperature	-40°C to 70°C
Relative Humidity	10% to 90% (non-condensing)
Input Voltage Range	100-240V AC
Compliance	FCC Part 15 Class A, ICES-003 Class A, CE
Product Code	Juniper EX2300-C-12P-VC
Brand	Juniper

Replacement / Alternative Options

If the Juniper EX2300-C-12P-VC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.

Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG
-------------------------------	---

Request availability: [Ask for current stock](#) of Juniper EX2300-C-12P-VC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).