

Juniper EX9214-RED3A-AC-T Switches

Model: Juniper EX9214-RED3A-AC-T | Brand: Juniper

Product Overview

Redundant EX9214 TAA system configuration: 14-slot chassis with passive midplane and 2x fan trays, 2x routing engines, 3x switch fabric-2 modules, 4x 4100W AC PSUs, and all necessary blank panels

Product page: <https://www.linknewnet.com/products/juniper-ex9214-red3a-ac-t>

Quick Specifications

Attribute	Value
Brand	Juniper
Product Name	Juniper EX9214-RED3A-AC-T
Category	Networking/Chassis Switch
Chassis Configuration	14-slot chassis with passive midplane
Fan Trays	2x fan trays
Routing Engines	2x routing engines
Switch Fabric Modules	3x switch fabric-2 modules
Power Supply Units (PSUs)	4x 4100W AC PSUs
Compliance	TAA
Blank Panels	Included for all necessary slots
Power Redundancy	Yes
Cooling	Redundant cooling with 2 fan trays
Operating Environment	Enterprise and Data Center
Physical Security	Tamper-proof hardware components
Management Ports	Dedicated RJ-45 and console ports
Software Compatibility	Junos OS
Virtual Chassis Capability	Supports forming a virtual chassis with other EX Series switches
Networking Standards	IEEE 802.1Q, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ae
Layer 3 Features	Static routing, OSPF, BGP, Multicast
Security Features	Dynamic ARP inspection, IP source guard, MACsec support
Product Code	Juniper EX9214-RED3A-AC-T
Brand	Juniper

Replacement / Alternative Options

If the Juniper EX9214-RED3A-AC-T is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.

Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG
-------------------------------	---

Request availability: [Ask for current stock](#) of Juniper EX9214-RED3A-AC-T or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).