

Juniper EX9253-RED-DC Switches

Model: Juniper EX9253-RED-DC | Brand: Juniper

Product Overview

Redundant EX9253 configuration: 3-slot JNP-C1-CHAS-3RU chassis with 4 fan tray JAN-FAN-3RU, 2x routing engine EX9253-RE, 4x JNP-PWR1100-DC-BB DC PSUs, and all necessary blank panels

Product page: <https://www.linknewnet.com/products/juniper-ex9253-red-dc>

Quick Specifications

Attribute	Value
Product Name	Juniper EX9253-RED-DC
Configuration	Redundant configuration
Chassis	3-slot JNP-C1-CHAS-3RU
Fan Tray	4x JAN-FAN-3RU
Routing Engines	2x EX9253-RE
Power Supply Units	4x JNP-PWR1100-DC-BB DC
Blank Panels	Included
Power Requirement	DC Power Configuration
Slots	3-Slots available for modular components
Form Factor	3RU
Cooling	Redundant fan tray setup for optimal cooling
Power Redundancy	Full power redundancy with 4 power supply units
Management	Out-of-band management supported
Network Interfaces	Depends on installed modules/cards
Software Compatibility	Juniper Networks Junos operating system
Reliability	Highly reliable design targeted for network infrastructure
Target Use	Enterprise and Data Center networks
Expandability	Modular design for scale-out options
Compliance	Standards compliant for network hardware
Warranty	Standard manufacturer warranty
Product Code	Juniper EX9253-RED-DC
Brand	Juniper

Replacement / Alternative Options

If the Juniper EX9253-RED-DC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.

Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG
-------------------------------	---

Request availability: [Ask for current stock](#) of Juniper EX9253-RED-DC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).