

Juniper JNP-25G-AOC-30M Switches

Model: Juniper JNP-25G-AOC-30M | Brand: Juniper

Product Overview

SFP28, 25GE Active Optical Cable, 30 meters, Standard Temperature (0 through 70 DEGREE C), 1.5W, Pull Tab

Product page: <https://www.linknewnet.com/products/juniper-jnp-25g-aoc-30m>

Quick Specifications

Attribute	Value
Brand	Juniper
Product Name	Juniper JNP-25G-AOC-30M
Interface Type	SFP28
Data Rate	25 Gigabit Ethernet (25GE)
Cable Type	Active Optical Cable
Cable Length	30 meters
Temperature Range	Standard Temperature (0 through 70 DEGREE C)
Power Consumption	1.5W
Connector Type	Pull Tab
Compatibility	Compatible with Juniper Networks devices that support SFP28 transceivers
Certifications	Meets relevant industry standards for SFP28 interfaces
Operational Humidity	Standard operational humidity levels suitable for data center environments
Electrical Interface	Compliant with SFP28 MSA
Wavelength	Optical wavelength specified for 25GE transmission
Modulation	Appropriate modulation method for 25GE
Connector Material	High-quality connector materials for optimal signal transmission
Cable Jacket Material	Durable materials suitable for intensive use in various environments
Compliance	Environmentally compliant; RoHS
Security Features	Incorporates security features for authentication and encryption
Physical Form Factor	Designed for high-density network environments
Product Code	Juniper JNP-25G-AOC-30M
Brand	Juniper

Replacement / Alternative Options

If the Juniper JNP-25G-AOC-30M is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.
Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG

Request availability: [Ask for current stock](#) of Juniper JNP-25G-AOC-30M or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).