

Juniper QFX10002-36Q-DC Switches

Model: Juniper QFX10002-36Q-DC | Brand: Juniper

Product Overview

QFX10002 System with 36-port 40G QSFP+ / 12-port 100G QSFP28 / 144-port 10G SFP+ with 2 1600W DC Power Supplies, 2 power cables and 3 Fan Trays

Product page: <https://www.linknewnet.com/products/juniper-qfx10002-36q-dc>

Quick Specifications

Attribute	Value
Brand	Juniper
Model	QFX10002-36Q-DC
Form Factor	Fixed Platform
Ports	36-port 40G QSFP+ / 12-port 100G QSFP28 / 144-port 10G SFP+
Power Supplies	2 x 1600W DC
Number of Power Cables	2
Fan Trays	3
Switching Capacity	Adjustable - Based on configuration
Data Plan Rate (Per Slot)	Adjustable - Based on usage
JUNOS Version Supported	Latest or specific release suitable for the model
Layer 3 Features	Comprehensive IPv4/IPv6, MPLS and VPLS support
Layer 2 Features	Extensive VLAN, LAG with LACP, Q-in-Q, and MAC table capabilities
Latency	Dependent on port speed and type of media
Operational Temperature	0■■■C to 40■■■C (32■■■F to 104■■■F)
Storage Temperature	-40■■■C to 70■■■C (-40■■■F to 158■■■F)
Humidity	10% to 85% non-condensing
LED Indicators	Status, Activity, Link
Virtual Chassis Configurations	Supported with appropriate license
Security Features	AES, MACsec, and more based on Junos OS
Management	Console, SSH, SNMP, Junos Space, and J-Web Interface
Product Code	Juniper QFX10002-36Q-DC
Brand	Juniper

Replacement / Alternative Options

If the Juniper QFX10002-36Q-DC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.

Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG
-------------------------------	---

Request availability: [Ask for current stock](#) of Juniper QFX10002-36Q-DC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).