

Juniper QFX5110-32Q-AFI2 Switches

Model: Juniper QFX5110-32Q-AFI2 | Brand: Juniper

Product Overview

32 QSFP+/20 QSFP+ QSFP28, back to front air flow, AC
Product page: <https://www.linknewnet.com/products/juniper-qfx5110-32q-afi2>

Quick Specifications

Attribute	Value
Brand	Juniper
Model	QFX5110-32Q-AFI2
Port Configuration	32 QSFP+ / 20 QSFP+ QSFP28
Airflow	Back to Front
Power Supply	AC
Switch Capacity	6.4 Tbps
Packet Forwarding Capacity	2.4 Bpps
Layer 2 Features	VLAN, Spanning Tree Protocol (STP), Link Aggregation (LAG)
Layer 3 Features	OSPF, BGP, VRRP, RIP
Management	CLI, Web GUI, SNMP
Operating Temperature	0°C to 40°C
Storage Temperature	-40°C to 70°C
Relative Humidity	5% to 95% (non-condensing)
Dimensions (WxHxD)	17.5 x 1.75 x 18 in (44.5 x 4.4 x 45.7 cm)
Forwarding Modes	Store-and-Forward
Redundancy	Power Supply, Fan
Junos OS	Yes
Max Power Consumption	500W
LED Indicators	Power, Status, Port Link, Port Activity
Mount Type	Rack Mount
Product Code	Juniper QFX5110-32Q-AFI2
Brand	Juniper

Replacement / Alternative Options

If the Juniper QFX5110-32Q-AFI2 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.
Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG

Request availability: [Ask for current stock](#) of Juniper QFX5110-32Q-AFI2 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).