

Juniper QFX5110-32Q-D-AFI2 Switches

Model: Juniper QFX5110-32Q-D-AFI2 | Brand: Juniper

Product Overview

32 QSFP+/20 QSFP+ QSFP28, back to front air flow, DC

Product page: <https://www.linknewnet.com/products/juniper-qfx5110-32q-d-afi2>

Quick Specifications

Attribute	Value
Brand	Juniper
Model	QFX5110-32Q-D-AFI2
Port Configuration	32 QSFP+/20 QSFP+ QSFP28
Airflow	Back to Front
Power Supply	DC
Switching Capacity	2.56 Tbps
Forwarding Rate	1905 Mpps
Latency	~650 ns
VLAN IDs	4094
Queue Schedules	Strict Priority, Shaped Deficit Weighted Round Robin
Jumbo Frame Support	Up to 9216 bytes
MAC Address Table Size	288,000 entries
Dimensional Size	1.72 x 17.64 x 18.66 in
Power Consumption	500W
Environment	Operating Temperature: 0 to 40°C
Cooling	Back-to-Front Airflow
Redundancy	Power Supply and Fan Module Redundancy
Management	Juniper Junos OS
Layer Support	Layer 2 and Layer 3 Features
Forwarding Engine	Advanced Packet Forwarding with Deep Buffer Capacity
Product Code	Juniper QFX5110-32Q-D-AFI2
Brand	Juniper

Replacement / Alternative Options

If the Juniper QFX5110-32Q-D-AFI2 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.
Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG

Request availability: [Ask for current stock](#) of Juniper QFX5110-32Q-D-AFI2 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).