

Juniper QFX5130-32CD-AFI Switches

Model: Juniper QFX5130-32CD-AFI | Brand: Juniper

Product Overview

32 X 400G 1U PSU side intake and port side exhaust

Product page: <https://www.linknewnet.com/products/juniper-qfx5130-32cd-afi>

Quick Specifications

Attribute	Value
Brand	Juniper
Model	QFX5130-32CD-AFI
Ports	32 x 400G
Form Factor	1U
Cooling Design	PSU side intake and port side exhaust
Power Supply	Redundant, hot-swappable
Layer	Layer 3
Switching Capacity	25.6 Tbps
Forwarding Rate	10 Bpps
Latency	< 1 microsecond
Buffer Size	42 MB
Jumbo Frame Support	Up to 9216 bytes
MAC Addresses	160,000
VLANs	4,096
Operating Temperature	0°C to 40°C
Storage Temperature	-40°C to 70°C
Humidity	5% to 90% (non-condensing)
AC Input Voltage	90-264V
Frequency	50/60Hz
Dimensions	42.8 x 4.39 x 57.5 cm
Product Code	Juniper QFX5130-32CD-AFI
Brand	Juniper

Replacement / Alternative Options

If the Juniper QFX5130-32CD-AFI is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.
Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG

Request availability: [Ask for current stock](#) of Juniper QFX5130-32CD-AFI or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).