

Juniper QFX5130-32CD-D-AFO Switches

Model: Juniper QFX5130-32CD-D-AFO | Brand: Juniper

Product Overview

32 X 400G 1U port side intake and PSU side exhaust, DC

Product page: <https://www.linknewnet.com/products/juniper-qfx5130-32cd-d-afo>

Quick Specifications

Attribute	Value
Brand	Juniper
Model	QFX5130-32CD-D-AFO
Port Configuration	32 x 400G
Form Factor	1U
Airflow	Port side intake and PSU side exhaust
Power Supply	DC
Switching Capacity	12.8 Tbps
Forwarding Capacity	4 Bpps
Latency	Low latency
Buffer Size	42 MB
Junos OS	Yes
Dimensions	1.75" x 19" x 20";
Management Interfaces	1 x RJ-45 serial console, 1 x RJ-45 management port, 1 x USB 2.0 port
Cooling	Front-to-back
Maximum Power Consumption	800W
MAC Address Table Size	100,000 entries
VLAN IDs	4,096
Routing Protocols	BGP, OSPF, IS-IS, RIP, Static
Security Features	ACL, MACsec
Environmental Operating Temperature	0°C to 40°C (32°F to 104°F)
Product Code	Juniper QFX5130-32CD-D-AFO
Brand	Juniper

Replacement / Alternative Options

If the Juniper QFX5130-32CD-D-AFO is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.

Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG
-------------------------------	---

Request availability: [Ask for current stock](#) of Juniper QFX5130-32CD-D-AFO or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).