

Juniper QFX5220-128C-D-AFO Switches

Model: Juniper QFX5220-128C-D-AFO | Brand: Juniper

Product Overview

128 x 100G 4U system with dual DC PSUs and Air Flow out

Product page: <https://www.linknewnet.com/products/juniper-qfx5220-128c-d-afo>

Quick Specifications

Attribute	Value
Brand	Juniper
Model	QFX5220-128C-D-AFO
Total Ports	128
Port Speed	100G
Form Factor	4U
Power Supply Units	Dual DC PSUs
Air Flow	Air Flow Out
Switching Capacity	12.8 Tbps
Forwarding Capacity	4.8 Bpps
Latency	< 550ns (nanoseconds)
Average Power Consumption	1200W
Dimensions (H x W x D)	7.0 x 17.6 x 21.5 inches
Operating Temperature Range	0°C to 40°C
Storage Temperature Range	-40°C to 70°C
Operating Humidity	5% to 90% (non-condensing)
Storage Humidity	0% to 95% (non-condensing)
Management Ports	1 x Console, 1 x Management Ethernet
Supported Optics	QSFP28, QSFP+, SFP28
Cooling Fans	Front-to-back airflow
Network Protocols	IPv4, IPv6
Product Code	Juniper QFX5220-128C-D-AFO
Brand	Juniper

Replacement / Alternative Options

If the Juniper QFX5220-128C-D-AFO is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
Juniper EX-QFX-MACSEC-AGG	MACSec SW Feature License on Aggregation Switches. Applicable to EX4550 Switches.
Juniper EX-SFP-10GE-DAC-1M	SFP+, 10GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.57W, 30 AWG

Request availability: [Ask for current stock](#) of Juniper QFX5220-128C-D-AFO or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).