

Huawei S2300 Series Switch LS-S2318TP-EI-AC

Model: LS-S2318TP-EI-AC | Brand: HUAWEI

Product Overview

S2318TP-EI Mainframe(16 10/100 BASE-T ports and 2 Combo GE(10/100/1000 BASE-T+100/1000 Base-X) ports and AC 110/220V)

Product page: <https://www.linknewnet.com/products/ls-s2318tp-ei-ac>

Quick Specifications

Attribute	Value
Port	sixteen 10/100Base-TX ports and two gigabit Combo ports (10/100/1000Base-T or 100/1000Base-X).
Forwarding performance	5.4 Mpps
Port switching capacity	7.2 Gbit/s
Backplane switching capacity	32 Gbit/s
IPv6 features	Supports IPv6 host functions. Supports static route configuration. Supports IPv6 ACL. Supports MLD v1/v2 snooping.
Multicast	Supports IGMP v1/v2/v3 snooping. Supports multicast load sharing among bundled ports. Supports port-based multicast rate limit and traffic statistics
Operating environment	Operating temperature: 0°C to 50°C (long term); -5°C to 55°C (short term); relative humidity: 10% to 90% (non-condensing)
Dimensions: width x depth x height	442 mm x 220 mm x 43.6 mm
Weight	< 2.4 kg
Power consumption	< 14.5 W
Product Code	LS-S2318TP-EI-AC
Brand	HUAWEI

Replacement / Alternative Options

If the LS-S2318TP-EI-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
LS-S2309TP-EI-AC	S2309TP-EI Mainframe(8 10/100 BASE-T ports and 1 Combo GE(10/100/1000 BASE-T+100/1000 Base-X) ports and AC 110/220V)
LS-S2309TP-EI-DC	S2309TP-EI Mainframe(8 10/100 BASE-T ports and 1 Combo GE(10/100/1000 BASE-T+100/1000 Base-X) ports and DC -48V)

Request availability: [Ask for current stock](#) of LS-S2318TP-EI-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).