

Huawei S3300 Series Switch LS-S3328TP-EI-24S-DC

Model: LS-S3328TP-EI-24S-DC | Brand: HUAWEI

Product Overview

S3328TP-EI-24S Mainframe(24 100 BASE-X ports and 2 Combo GE(10/100/1000 BASE-T+100/1000 BASE-X) ports and 2 SFP GE (1000 BASE-X) ports (SFP Req.) and DC -48V)

Product page: <https://www.linknewnet.com/products/ls-s3328tp-ei-24s-dc>

Quick Specifications

Attribute	Value
Specifications	Details
Product Model	LS-S3328TP-EI-24S-DC
Power Consumption	30 W
Switching capacity	12.8 Gbit/s
Forwarding performance	9.6 Mpps
DDR memory	128 MB
Flash Memory	16 MB
Backplane switching capacity	64 Gbit/s
Number of Ports	24 100 BASE-X ports, 2 Combo GE ports, and 2 SFP GE ports
Combo GE Port Type	10/100/1000 BASE-T+100/1000 BASE-X
VLAN Support	IEEE 802.1Q VLAN, MAC VLAN, and protocol-based VLAN
Management Interface	Console port, Telnet, SSH, and SNMP
Processor	Dominant frequency: 300 MHz
Dimensions: width x depthx height	442 x 420 x43.6mm
VLAN features	Supports up to 4096 VLANs.
Product Code	LS-S3328TP-EI-24S-DC
Brand	HUAWEI

Replacement / Alternative Options

If the LS-S3328TP-EI-24S-DC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
LS-S3328TP-EI-24S-AC	S3328TP-EI-24S Mainframe(24 100BASE-X ports and 2 Combo GE(10/100/1000 BASE-T+100/1000 BASE-X) ports and 2 SFP GE (1000 BASE-X) ports (SFP Req.) and A
LS-S3328TP-EI-AC	S3328TP-EI Mainframe(24 10/100 BASE-T ports and 2 Combo GE(10/100/1000 BASE-T+100/1000 Base-X) ports and 2 SFP GE (1000 BASE-X) ports (SFP Req.) and A

Request availability: [Ask for current stock](#) of LS-S3328TP-EI-24S-DC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).