

Huawei S3300 Series Switch LS-S3352P-EI-48S-AC

Model: LS-S3352P-EI-48S-AC | Brand: HUAWEI

Product Overview

S3352P-EI-48S Mainframe(48 100 BASE-X ports and 2 100/1000 BASE-X ports and 2 SFP GE (1000 BASE-X) ports (SFP Req.) and AC 110/220V)

Product page: <https://www.linknewnet.com/products/ls-s3352p-ei-48s-ac>

Quick Specifications

Attribute	Value
Forwarding performance	13.2 Mpps
Port switching capacity	17.6 Gbit/s
Backplane switching capacity	64 Gbit/s
Weight	< 4.8 kg
Power consumption	< 92 W
Dimensions: width x depth x height	442 mm x 420 mm x 43.6 mm
Port	forty-eight 100Base-FX SFP ports, two 100/1000Base-X SFP ports, and two 1000Base-X SFP ports
IPv4 routing	Supports static routing, RIP v1, RIP v2, and ECMP. Supports OSPF, IS-IS, and BGP.
IPv6 routing	Supports static routing, RIPng, and OSPF v3.
Operating environment	Operating temperature: 0°C to 50°C (long term); -5°C to 55°C (short term); relative humidity: 10% to 90% (non-condensing)
Product Code	LS-S3352P-EI-48S-AC
Brand	HUAWEI

Replacement / Alternative Options

If the LS-S3352P-EI-48S-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
LS-S3328TP-EI-24S-AC	S3328TP-EI-24S Mainframe(24 100BASE-X ports and 2 Combo GE(10/100/1000 BASE-T+100/1000 BASE-X) ports and 2 SFP GE (1000 BASE-X) ports (SFP Req.) and A
LS-S3328TP-EI-24S-DC	S3328TP-EI-24S Mainframe(24 100 BASE-X ports and 2 Combo GE(10/100/1000 BASE-T+100/1000 BASE-X) ports and 2 SFP GE (1000 BASE-X) ports (SFP Req.) and

Request availability: [Ask for current stock](#) of LS-S3352P-EI-48S-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).