

Huawei S5300 Series Switch LS-S5324TP-SI-DC

Model: LS-S5324TP-SI-DC | Brand: HUAWEI

Product Overview

S5324TP-SI-DC Mainframe(24 10/100/1000Base-T,4 100/1000Base-X Combo,DC -48V)

Product page: <https://www.linknewnet.com/products/ls-s5324tp-si-dc>

Quick Specifications

Attribute	Value
PoE	No
Memory (RAM)	256 MB
Flash	32 MB
Mean time between failures (MTBF)	37 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Rated voltage range	-48 V DC to -60 V DC
Maximum voltage range	-36 V DC to -72 V DC
Service port surge protection	±2 kV in common mode
Stack ports	Two stack ports available on each stack card
Power supply surge protection	±1 kV in differential mode; ±2 kV in common mode
Dimensions (W x D x H)	442.0 mm x 220.0 mm x 43.6 mm
Weight	Fully loaded:≤ 8.5 kg Empty loaded:≤ 5 kg
Maximum stack bandwidth (bidirectional)	48 Gbit/s
Product Code	LS-S5324TP-SI-DC
Brand	HUAWEI

Replacement / Alternative Options

If the LS-S5324TP-SI-DC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
LS-S5324TP-PWR-SI	S5324TP-PWR-SI Mainframe(24 10/100/1000Base-T,4 100/1000Base-X Combo,PoE,Chassis,Dual Slots of power,Without Power Module)
LS-S5324TP-SI-AC	S5324TP-SI-AC Mainframe(24 10/100/1000Base-T,4 100/1000Base-X Combo,AC 110/220V)

Request availability: [Ask for current stock](#) of LS-S5324TP-SI-DC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).