

Huawei S5300 Series Switch LS-S5328C-HI-24S

Model: LS-S5328C-HI-24S | Brand: HUAWEI

Product Overview

S5328C-HI-24S Mainframe (24 100/1000Base-X, Chassis, Dual Slots of power, Without Flexible Card and Power Module)

Product page: <https://www.linknewnet.com/products/ls-s5328c-hi-24s>

Quick Specifications

Attribute	Value
PoE	No
Memory (RAM)	512 MB
Flash	64 MB
Dimensions (W x D x H)	442.0 mm x 220.0 mm x 43.6 mm
Maximum stack bandwidth (bidirectional)	80 Gbit/s
Mean time between failures (MTBF)	25.5 years when a 4x10GE card is configured; 34.8 years when a 2x10GE card is configured; 36.1 years when a 4xGE card is configured
Power supply protection	AC: ±6 kV in differential mode; ±6 kV in common mode DC: ±1 kV in differential mode; ±2 kV in common mode
Weight	Fully loaded:≤ 6.5 kg Empty loaded:≤ 5 kg
Stack ports	Versions earlier than V200R003C00 do not support stack ports. Since V200R003C00, the 10GE ports on the front card can be used as stack ports.
Rated voltage range	-48 V DC to -60 V DC 100 V AC to 240 V AC, 50/60 Hz
Maximum voltage range	-36 V DC to -72 V DC 90 V AC to 264 V AC, 47 Hz to 63 Hz
Product Code	LS-S5328C-HI-24S
Brand	HUAWEI

Replacement / Alternative Options

If the LS-S5328C-HI-24S is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
LS-S5324TP-PWR-SI	S5324TP-PWR-SI Mainframe(24 10/100/1000Base-T,4 100/1000Base-X Combo,PoE,Chassis,Dual Slots of power,Without Power Module)
LS-S5324TP-SI-AC	S5324TP-SI-AC Mainframe(24 10/100/1000Base-T,4 100/1000Base-X Combo,AC 110/220V)

Request availability: [Ask for current stock](#) of LS-S5328C-HI-24S or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).