

Huawei S5300 Series Switch LS-S5328C-HI

Model: LS-S5328C-HI | Brand: HUAWEI

Product Overview

S5328C-HI Mainframe (24 10/100/1000Base-T, Chassis, Dual Slots of power, Without Flexible Card and Power Module)

Product page: <https://www.linknewnet.com/products/ls-s5328c-hi>

Quick Specifications

Attribute	Value
Fixed port	24 10/100/1000Base-T ports
Forwarding performance	96 Mpps
Extended slot	provides an extended slot for an uplink subcard
MPLS	MPLS, MPLS VLL,L3VPN
VPLS	Martini VPLS
Dimensions (mm)	442 mm x 220 mm x 43.6 mm
Typical power consumption	< 76 W
IP routing	Static routing, RIPv1, RIPv2, OSPF, IS-IS, BGP, and ECMP
Operating environment	Operating temperature: 0 o C–50 o C (long term); -5 o C–55 o C (short term) Relative humidity: 10%–90% (non-condensing)
Product Code	LS-S5328C-HI
Brand	HUAWEI

Replacement / Alternative Options

If the LS-S5328C-HI is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
LS-S5324TP-PWR-SI	S5324TP-PWR-SI Mainframe(24 10/100/1000Base-T,4 100/1000Base-X Combo,PoE,Chassis,Dual Slots of power,Without Power Module)
LS-S5324TP-SI-AC	S5324TP-SI-AC Mainframe(24 10/100/1000Base-T,4 100/1000Base-X Combo,AC 110/220V)

Request availability: [Ask for current stock](#) of LS-S5328C-HI or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).