

MX240-PREMIUM3-DC - Juniper MX204/MX240/MX480 Routers

Model: MX240-PREMIUM3-DC | Brand: Juniper

Product Overview

MX240 Premium Chassis Bundle with Enhanced Midplane. Also includes redundant RE, redundant SCB-E, redundant DC Power

Product page: <https://www.linknewnet.com/products/mx240-premium3-dc>

Quick Specifications

Attribute	Value
Product Name	MX240-PREMIUM3-DC
Brand	Juniper
Chassis	MX240 Premium Chassis Bundle with Enhanced Midplane
Redundant Routing Engines	Included
Redundant Switch Control Boards (SCB-E)	Included
Redundant Power Supplies	Redundant DC Power
Power Supply Specifications	DC input
Maximum Power Consumption	2200 watts
Rack Units (RU)	5 RU
Physical Dimensions	8.71 x 17.42 x 23.50 inches (H x W x D)
Cooling	Front-to-back cooling
Maximum Operating Temperature	40°C
Minimum Operating Temperature	0°C
Storage Temperature	-40°C to 70°C
Operating Humidity	5% to 90% (non-condensing)
Number of Slots	2 slots
Network Interfaces	Various types based on Modular Interface Cards
Control Plane Redundancy	Supported with dual Routing Engines
Forwarding Plane Redundancy	Supported with dual SCB-E
Compliance	RoHS-6, NEBS
Product Code	MX240-PREMIUM3-DC
Brand	Juniper

Replacement / Alternative Options

If the MX240-PREMIUM3-DC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
MX240-PREM3-AC	MX240 AC Premium Fully Redundant "Built to Stock" System with dual Switch control board (SCBE), dual RE-S-1800X4-16G, redundant AC Power and Fan trays
MX240-PREM3-DC	MX240 DC Premium Fully Redundant "Built to Stock" System with dual Switch control board (SCBE), dual RE-S-1800X4-16G, redundant DC Power and Fan trays

Request availability: [Ask for current stock](#) of MX240-PREMIUM3-DC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).