

MX960-PREM3AC-ECM - Juniper MX960 5G Universal Routing Platforms

Model: MX960-PREM3AC-ECM | Brand: Juniper

Product Overview

MX960 AC Premium Fully Redundant "Built to Stock" System with three Switch control board (SCBE), dual RE-S-1800X4-16G, redundant AC Power and Fan trays, and Extended Cable Manager

Product page: <https://www.linknewnet.com/products/mx960-prem3ac-ecm>

Quick Specifications

Attribute	Value
Product Type	AC Premium Fully Redundant System
Switch Control Board	Three (SCBE)
Routing Engine	Dual RE-S-1800X4-16G
Power Supply	Redundant AC Power
Fan Trays	Redundant Fan Trays
Extended Cable Manager	Included
Layer Support	Layer 2 and Layer 3
Maximum Throughput	Up to 960 Gbps per slot
Ports	Variety including Ethernet, SONET/SDH, ATM, T1/E1, etc.
Rack Units	16U
Operating Temperature	32° to 104°F (0° to 40°C)
Storage Temperature	-40° to 158°F (-40° to 70°C)
Relative Humidity	5% to 90% (non-condensing)
Management Ports	RJ-45, Console, AUX
Power Consumption	Up to 10,000 Watts
Software	Junos OS
Redundancy	Fully Redundant
Dimensions (H x W x D)	27.8 x 17.5 x 23.5 inches
MTBF	300,000 hours
Regulatory Compliance	FCC, CE, UL, NEBS
Product Code	MX960-PREM3AC-ECM
Brand	Juniper

Replacement / Alternative Options

If the MX960-PREM3AC-ECM is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
MX960-BASE-AC	MX960 Base Chassis with Midplane, 2 nos. SCB-E, AC Power, Discounted RE incl. Junos

MX960-P3-SCBE2-ECM	MX960 AC Premium Fully Redundant "Built to Stock" System with three Switch control board (SCBE2), dual RE-S-1800X4-16G, redundant AC Power and Fan tra
--------------------	--

Request availability: [Ask for current stock](#) of MX960-PREM3AC-ECM or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).