

NIM-2BRI-S/T - Cisco C8000 network interface module

Model: NIM-2BRI-S/T | Brand: CISCO

Product Overview

2-port ISDN BRI WAN interface card for Data

Product page: <https://www.linknewnet.com/products/nim-2bri-s-t>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	NIM-2BRI-S/T
Interface	ISDN BRI
Port Count	2
Application	WAN
Data Transfer Rate	Up to 144 Kbps per BRI
Form Factor	Plug-in module
Compatibility	Cisco 4000 Series Integrated Services Routers (ISR)
Protocol Support	ISDN, PPP, Frame Relay
Dimensions	78 x 123 x 18 mm
Power Requirements	Powered by the host router
Operating Temperature	0 to 40°C (32 to 104°F)
Storage Temperature	-40 to 70°C (-40 to 158°F)
Humidity	10% to 90% non-condensing
MTBF (Mean Time Between Failures)	1,000,000 hours
Certifications	CE, FCC Class B, ICES-003
Warranty	Limited lifetime
Connector Type	RJ-45
Max Power Consumption	3.5W
LED Indicators	Status, Activity
Product Code	NIM-2BRI-S/T
Brand	CISCO

Replacement / Alternative Options

If the NIM-2BRI-S/T is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
NIM-2BRI-NT/TE	2-Port BRI Network Interface Module
NIM-2BRI-NT/TE=	2-port BRI Network Interface Module

Request availability: [Ask for current stock](#) of NIM-2BRI-S/T or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).