

NIM-4G-LTE-GA= - Cisco ISR4000 Network Interface Modules

Model: NIM-4G-LTE-GA= | Brand: CISCO

Product Overview

Cisco 4G LTE NIM for Global (Europe, Australia & New Zealand)

Product page: <https://www.linknewnet.com/products/nim-4g-lte-ga>

Quick Specifications

Attribute	Value
Connectivity	4G LTE
Supported Regions	Global (Europe, Australia, New Zealand)
Antenna Ports	2
Max Downlink Speed	150 Mbps
Max Uplink Speed	50 Mbps
LTE Bands	B1, B3, B7, B8, B20
3G Bands	B1, B8
SIM Slot	1 Standard SIM (2FF)
Operating Temperature Range	-40°C to 60°C (-40°F to 140°F)
Storage Temperature Range	-40°C to 85°C (-40°F to 185°F)
Humidity	5% to 95% (non-condensing)
Dimensions	7.28 x 5.51 x 1.06 inches (185 x 140 x 27 mm)
Mounting Options	Rack-mountable
Certification	CE, RoHS
Management	CLI, Cisco SD-WAN
Modem Chipset	Qualcomm
Power Supply	External, DC: 12V
Power Consumption	15W max
Firmware Upgrades	OTA (Over-The-Air)
Security Features	VPN, Firewall, QoS
Product Code	NIM-4G-LTE-GA=
Brand	CISCO

Replacement / Alternative Options

If the NIM-4G-LTE-GA= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC
-----------	---

Request availability: [Ask for current stock](#) of NIM-4G-LTE-GA= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).