

NIM-4SHDSL-EA - Cisco Multimode Network Interface Module

Model: NIM-4SHDSL-EA | Brand: CISCO

Product Overview

Multi-mode G.SHDSL NIM

Product page: <https://www.linknewnet.com/products/nim-4shdsl-ea>

Quick Specifications

Attribute	Value
Product Name	Cisco NIM-4SHDSL-EA
Type	Multi-mode G.SHDSL NIM
Supported Interfaces	4-wire G.SHDSL, 2-wire G.SHDSL
Max Data Rate	15 Mbps (per port)
Ports	4 ports
Compatibility	Cisco ISR 4000 Series Routers, ISR 1000 Series Routers
Management	SNMP v3, CLI
Power Requirement	13.2W maximum
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Humidity	5% to 95% non-condensing
Dimensions	22.35 x 39.37 x 22.35mm
Layer	Layer 2 and Layer 3
MTBF	1,000,000 hours
Compliance	ITU-T G.991.2, IEEE 802.3
Security	Encryption, Port Security
DoS Protection	Supported
LED Indicators	Activity, Status
QoS	Advanced QoS Features
Product Code	NIM-4SHDSL-EA
Brand	CISCO

Replacement / Alternative Options

If the NIM-4SHDSL-EA is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module
WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC

Request availability: [Ask for current stock](#) of NIM-4SHDSL-EA or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).