

NIM-ES2-8 - Cisco ISR4000 Network Interface Modules

Model: NIM-ES2-8 | Brand: CISCO

Product Overview

8-port Layer 2 Gigabit Ethernet LAN Switch NIM

Product page: <https://www.linknewnet.com/products/nim-es2-8>

Quick Specifications

Attribute	Value
Product Number	NIM-ES2-8
Form Factor	Single-wide NIM form factor
Dimensions (H x W x D)	0.8 x 6.2 x 4.8 in. (2.1 x 18.8 x 12.2 cm)
Weight	108g (0.24 lb)
RFC	RFC 2284, PPP Extensible Authentication Protocol (EAP)
LED indicators	● Link status LED: One LED per port for indicating link status ● PoE LED: One LED per port system for PoE status indication
Internal power supply	Optional PoE system power supply available for all Cisco 4000 Series routers
Internal redundant power supply	For the Cisco 4431 and 4451 routers only
DC power support	● DC system power input available on the Cisco 4351, 4431, and 4451 routers ● PoE option not available with DC system power input
Software support	Minimum Cisco IOS-XE Software Release 3.15 for Cisco 4000 Series routers: IP Base License of the Universal image
Operating temperature	32° to 104°F (0° to 40°C)
Operating humidity	10 to 90 percent, noncondensing
Nonoperating temperature	-4° to 149°F (-20° to 65°C)
Operating altitude	15,000 ft (4,570m)
Product Code	NIM-ES2-8
Brand	CISCO

Replacement / Alternative Options

If the NIM-ES2-8 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
NIM-ES2-4=	4-port Layer 2 Gigabit Ethernet LAN Switch NIM
NIM-ES2-8-P	8-port PoE/PoE+ Layer 2 Gigabit Ethernet LAN Switch NIM

Request availability: [Ask for current stock](#) of NIM-ES2-8 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).