

NIM-PVDM-64 - Cisco Network Interface Module Slot

Model: NIM-PVDM-64 | Brand: CISCO

Product Overview

64-channel Voice DSP NIM Module

Product page: <https://www.linknewnet.com/products/nim-pvdm-64>

Quick Specifications

Attribute	Value
DSP	Multicore DSP technology
Interface	Network Interface module
Operating temperature	32° to 122°F (0° to 50°C)
Voltage	12V
Current	1.25A
Power	15W
Weight	0.45lb (204 g)
Dimensions (H x W x D)	1.25 x 3.50 x 7.24 in. (3.18 x 8.89 x 18.39 cm)
Homologation	Platform dependent
Mean time between failures (MTBF)	System dependent
Emissions	● CISPR32, Class A ● EN55032, Class A, CFR47, Part 15, Subpart B, Class A
Harmonics	EN61000-3-2
Flicker	EN61000-3-3
Immunity	● CISPR24 ● EN 55024 ● EN61000-6-1
Electrostatic discharge (ESD)	EN 61000-4-2
Surge	EN 61000-4-5
Conducted RF	EN 61000-4-6
Power-frequency magnetic fields	EN 6100-4-8
RF fields	EN 61000-4-3
EFT	EN 61000-4-4
Product Code	NIM-PVDM-64
Brand	CISCO

Replacement / Alternative Options

If the NIM-PVDM-64 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
NIM-PVDM-128	128-channel Voice DSP NIM Module

NIM-PVDM-256	256-channel Voice DSP NIM Module
--------------	----------------------------------

Request availability: [Ask for current stock](#) of NIM-PVDM-64 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).