

NIM-VAB-A - Cisco Multimode Network Interface Module

Model: NIM-VAB-A | Brand: CISCO

Product Overview

Multi-mode VDSL2/ADSL/2/2+ NIM Annex A

Product page: <https://www.linknewnet.com/products/nim-vab-a>

Quick Specifications

Attribute	Value
Product Name	NIM-VAB-A
Model	Annex A
Interface	Multi-mode VDSL2/ADSL/2/2+
Network Interface Module (NIM)	Yes
Compatibility	Compatible with ISR 4000 Series
VDSL2 Profile	17a, 30a
Fallback Option	ADSL2/2+
Maximum Downstream Rate	100 Mbps (VDSL2)
Maximum Upstream Rate	50 Mbps (VDSL2)
DSL Mode	Asynchronous
ATM Support	Yes
G.INP Support	Yes
G.Vector Support	Yes
ADSL Standards Supported	Annex A, B
Line Bonding	No
Operational Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 65°C (-4°F to 149°F)
Humidity	10% to 85% non-condensing
Dimensions	7.2 x 6.1 x 1.4 inches
Product Code	NIM-VAB-A
Brand	CISCO

Replacement / Alternative Options

If the NIM-VAB-A is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
NIM-VA-B	Multi-mode VDSL2/ADSL/2/2+ NIM Annex B
NIM-VAB-M	Multi-mode VDSL2/ADSL/2/2+ NIM Annex M

Request availability: [Ask for current stock](#) of NIM-VAB-A or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).