

NM-1T3/E3 - Cisco Interface Card Network Modules

Model: NM-1T3/E3 | Brand: CISCO

Product Overview

One port T3/E3 network module Cisco Router Network Module

Product page: <https://www.linknewnet.com/products/nm-1t3-e3>

Quick Specifications

Attribute	Value
Port Count	One port
Interface Type	T3/E3
Compatible Routers	Cisco 2600, 3600, and 3700 series
Data Rate	Up to 34.368 Mbps (E3) / 44.736 Mbps (T3)
Protocols Supported	HDLC, PPP
Form Factor	Internal module
Full-Duplex	Yes
Connector Type	BNC
Clocking	Internal and external
Maximum Distance	450 feet (internal clocking), 655 feet (external clocking)
Encapsulation Methods	Frame Relay, ATM, Transparent HDLC
Error Correction	BIP (Bit Interleaved Parity)
Redundancy Support	No (single module)
Installation Type	Plug and play
Environmental Operating Range	32°F to 104°F (0°C to 40°C)
Storage Temperature Range	-4°F to 149°F (-20°C to 65°C)
Humidity Range (operating)	10% to 85% non-condensing
Industry Standards	IEEE, ITU-T
Power Requirements	5V DC, 1.8A
Dimensions (HxWxD)	1.75 x 7.3 x 7.5 inches
Product Code	NM-1T3/E3
Brand	CISCO

Replacement / Alternative Options

If the NM-1T3/E3 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC
-----------	---

Request availability: [Ask for current stock](#) of NM-1T3/E3 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).